



TekFlex® Powder

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations.
Revision Date: 02/28/2018 Date of Issue: 02/28/2018 Supersedes SDS Date: 05/01/2015 Version 2.0
Revision Impetus: Added Minova CHEMTREC account number to emergency number.

SECTION 1: IDENTIFICATION

Product Identifier

Product Name: TekFlex® Powder

Synonyms: One component of a two component patented flexible cement based sealant, TekFlex® Powder and TekFlex® Liquid. The hazards of the final sprayable cement based sealant, TekFlex® are similar to its components contained in the SDSs.

Intended Use of the Product

Mine sealant

Name, Address, and Telephone of the Responsible Party

USA:

Minova USA Inc.
150 Summer Court
Georgetown, KY 40324
T 502-863-6800

For SDS Requests:

Call 1-855-266-7422 or email sds.na@orica.com

www.minovaglobal.com

Emergency Telephone Number

Emergency number : For chemical emergencies (24 hour) involving transportation, spill, leak, release, fire or accidents **IN THE U.S. or CANADA CALL: CHEMTREC 1-800-424-9300, Minova CCN 14730.**

Canada:

Minova
576 Arvin Avenue
Stoney Creek, ON - Canada L8E 5P1
T 905-643-1166

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Skin Irrit. 2 H315

Skin Sens. 1 H317

Eye Irrit. 2A H319

STOT SE3 H335

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

: H315 – Causes skin irritation.
H317 – May cause an allergic skin reaction.
H319 – Causes serious eye irritation.
H335 – May cause respiratory irritation.

Precautionary Statements (GHS-US)

: P261 – Avoid breathing dust.
P264 – Wash hands, forearms, and exposed areas thoroughly after handling.
P280 – Wear protective clothing, protective gloves, eye protection.
P302+P352 – IF ON SKIN: Wash with plenty of soap and water.
P305+P351+P338 – If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 – Immediately call a Poison Center or doctor/physician.
P333+P313 – If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 – If eye irritation persists: Get medical advice/attention.
P362+P364 – Take off contaminated clothing and wash it before reuse.

TekFlex® Powder

Safety Data Sheet

Other Hazards Contains Portland cement or other caustic material which may cause an allergic skin reaction in sensitive individuals. Wet cement can dry the skin and cause chemical burns.

Other Hazards Not Contributing to the Classification: None

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

| Name | Product identifier | % (w/w) | Classification (GHS-US) |
|-----------------------------|---------------------|---------|--|
| Calcium sulfate | (CAS No) 7778-18-9 | 10 - 30 | Skin Irrit. 2, H315 Eye Dam. 1, H318 |
| Cement, alumina, chemicals | (CAS No) 65997-16-2 | 10 - 30 | Eye Irrit. 2A, H319 |
| Cement, portland, chemicals | (CAS No) 65997-15-1 | 10 - 30 | Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT SE 3, H335 |
| Calcium hydroxide | (CAS No) 1305-62-0 | 1 - 5 | Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 |

A range of concentration as prescribed by the Controlled Products Regulations has been used where necessary, due to varying composition. Full text of H-phrases: see section 16.

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Keep at rest and in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin Contact: Remove contaminated clothing. Rinse off affected area with water. Obtain medical attention if irritation develops or persists.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes. Immediately call a doctor/physician.

Ingestion: Rinse mouth. Do not induce vomiting. If spontaneous vomiting occurs, have victim lean forward with head positioned between legs to avoid breathing in of vomit, rinse mouth and have victim drink plenty of water. Immediately call a POISON CENTER or doctor/physician. Never give anything by mouth to an unconscious person.

Most Important Symptoms and Effects Both Acute and Delayed

General: Irritation can be serious and damage eyes, respiratory system and skin. May cause an allergic skin reaction.

Inhalation: Causes irritation to the respiratory tract.

Skin Contact: Causes skin irritation. Exposure may produce an allergic reaction.

Eye Contact: Causes serious eye irritation.

Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: Repeated and prolonged inhalation may damage lungs.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not flammable.

Explosion Hazard: Product is not explosive.

Reactivity: Wet cement is alkaline. TekFlex® Powder and TekFlex® Liquid react to form a flexible cement based sealant.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Firefighters should wear full protective gear.

TekFlex® Powder

Safety Data Sheet

Hazardous Combustion Products: Oxides of calcium and other metal oxides. As in all fires toxic and noxious fumes.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not get in eyes or on skin. Do not breathe dust.

For Non-Emergency Personnel

Protective Equipment: Use appropriate Personal Protection Equipment (PPE).

Emergency Procedures: Evacuate danger area.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: In the event of a spill or leak of material sweep up material. Avoid creating excessive dust and as with all spills, minimize material from entering water systems.

Environmental Precautions

Avoid release to the environment.

Methods and Material for Containment and Cleaning Up

For Containment: Avoid generation of dust during clean-up of spills.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: Good housekeeping is needed during storage, transfer, handling, and use of this material to avoid excessive dust accumulation. Never add material to this product unless instructed by Minova.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Always wash your hands immediately after handling this product, and once again before leaving the workplace.

Conditions for Safe Storage, Including Any Incompatibilities

Storage Conditions: Store in a dry, cool place.

Incompatible Materials: Acids.

Specific End Use(s)

Mine sealant.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

| Cement, portland, chemicals (65997-15-1) | | |
|--|--------------------------------------|--|
| USA ACGIH | ACGIH TWA (mg/m ³) | 1 mg/m ³ |
| USA OSHA | OSHA PEL (TWA) (mg/m ³) | 5 mg/m ³ |
| USA NIOSH | NIOSH REL (TWA) (mg/m ³) | 5 mg/m ³ |
| USA IDLH | US IDLH (mg/m ³) | 5000 mg/m ³ |
| Alberta | OEL TWA (mg/m ³) | 10 mg/m ³ |
| British Columbia | OEL TWA (mg/m ³) | 3 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica) |
| Manitoba | OEL TWA (mg/m ³) | 1 mg/m ³ |
| New Brunswick | OEL TWA (mg/m ³) | 10 mg/m ³ |
| Newfoundland & Labrador | OEL TWA (mg/m ³) | 1 mg/m ³ |
| Nova Scotia | OEL TWA (mg/m ³) | 1 mg/m ³ |
| Nunavut | OEL TWA (mg/m ³) | 10 mg/m ³ (total mass) |
| Northwest Territories | OEL TWA (mg/m ³) | 10 mg/m ³ (total mass) |
| Ontario | OEL TWA (mg/m ³) | 1 mg/m ³ (containing no Asbestos and <1% Crystalline silica) |
| Prince Edward Island | OEL TWA (mg/m ³) | 1 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica) |
| Québec | VEMP (mg/m ³) | 5 mg/m ³ (containing no Asbestos and <1% Crystalline silica) |
| Saskatchewan | OEL STEL (mg/m ³) | 20 mg/m ³ |

TekFlex® Powder

Safety Data Sheet

| | | |
|--------------|-------------------------------|----------------------|
| Saskatchewan | OEL TWA (mg/m ³) | 10 mg/m ³ |
| Yukon | OEL STEL (mg/m ³) | 20 mg/m ³ |
| Yukon | OEL TWA (mg/m ³) | 10 mg/m ³ |

| Calcium sulfate (7778-18-9) | | |
|-----------------------------|--------------------------------------|---|
| USA ACGIH | ACGIH TWA (mg/m ³) | 10 mg/m ³ |
| USA OSHA | OSHA PEL (TWA) (mg/m ³) | 5 mg/m ³ |
| USA NIOSH | NIOSH REL (TWA) (mg/m ³) | 5 mg/m ³ |
| Alberta | OEL TWA (mg/m ³) | 10 mg/m ³ |
| British Columbia | OEL TWA (mg/m ³) | 10 mg/m ³ |
| Manitoba | OEL TWA (mg/m ³) | 10 mg/m ³ |
| New Brunswick | OEL TWA (mg/m ³) | 10 mg/m ³ |
| Newfoundland & Labrador | OEL TWA (mg/m ³) | 10 mg/m ³ |
| Nova Scotia | OEL TWA (mg/m ³) | 10 mg/m ³ |
| Ontario | OEL TWA (mg/m ³) | 10 mg/m ³ |
| Prince Edward Island | OEL TWA (mg/m ³) | 10 mg/m ³ |
| Québec | VEMP (mg/m ³) | 5 mg/m ³ (containing no Asbestos and <1% Crystalline silica) |
| Saskatchewan | OEL STEL (mg/m ³) | 20 mg/m ³ |
| Saskatchewan | OEL TWA (mg/m ³) | 10 mg/m ³ |

| Calcium hydroxide (1305-62-0) | | |
|-------------------------------|--------------------------------------|----------------------|
| USA ACGIH | ACGIH TWA (mg/m ³) | 5 mg/m ³ |
| USA OSHA | OSHA PEL (TWA) (mg/m ³) | 5 mg/m ³ |
| USA NIOSH | NIOSH REL (TWA) (mg/m ³) | 5 mg/m ³ |
| Alberta | OEL TWA (mg/m ³) | 5 mg/m ³ |
| British Columbia | OEL TWA (mg/m ³) | 5 mg/m ³ |
| Manitoba | OEL TWA (mg/m ³) | 5 mg/m ³ |
| New Brunswick | OEL TWA (mg/m ³) | 5 mg/m ³ |
| Newfoundland & Labrador | OEL TWA (mg/m ³) | 5 mg/m ³ |
| Nova Scotia | OEL TWA (mg/m ³) | 5 mg/m ³ |
| Nunavut | OEL STEL (mg/m ³) | 10 mg/m ³ |
| Nunavut | OEL TWA (mg/m ³) | 5 mg/m ³ |
| Northwest Territories | OEL STEL (mg/m ³) | 10 mg/m ³ |
| Northwest Territories | OEL TWA (mg/m ³) | 5 mg/m ³ |
| Ontario | OEL TWA (mg/m ³) | 5 mg/m ³ |
| Prince Edward Island | OEL TWA (mg/m ³) | 5 mg/m ³ |
| Québec | VEMP (mg/m ³) | 5 mg/m ³ |
| Saskatchewan | OEL STEL (mg/m ³) | 10 mg/m ³ |
| Saskatchewan | OEL TWA (mg/m ³) | 5 mg/m ³ |
| Yukon | OEL STEL (mg/m ³) | 10 mg/m ³ |
| Yukon | OEL TWA (mg/m ³) | 5 mg/m ³ |

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment: Gloves. Protective clothing. Safety glasses. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Safety glasses or chemical goggles as appropriate to prevent eye contact.

Skin and Body Protection: Wear suitable protective clothing.

TekFlex® Powder

Safety Data Sheet

Respiratory Protection: Use a NIOSH-approved respirator “dust mask” when spraying this product or in dusty conditions or whenever exposure may exceed established Occupational Exposure Limits.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

| | |
|---|-------------------------------------|
| Physical State | : Solid |
| Appearance | : Grey powder |
| Odor | : None |
| Odor Threshold | : Not applicable |
| pH | : 10.5 - 11.5 when mixed with water |
| Relative Evaporation Rate (butyl acetate=1) | : Not applicable |
| Melting Point | : Not applicable |
| Freezing Point | : Not applicable |
| Boiling Point | : Not applicable |
| Flash Point | : Not applicable |
| Auto-ignition Temperature | : Not applicable |
| Decomposition Temperature | : Not applicable |
| Flammability (solid, gas) | : Not applicable |
| Lower Flammable Limit | : Not applicable |
| Upper Flammable Limit | : Not applicable |
| Vapor Pressure | : Not applicable |
| Relative Vapor Density at 20 °C | : Not applicable |
| Relative Density | : Not applicable |
| Specific Gravity | : Not applicable |
| Solubility | : Slightly soluble in water |
| Partition coefficient: n-octanol/water | : Not applicable |
| Viscosity | : Not applicable |
| Explosion Data – Sensitivity to Mechanical Impact | : Not applicable |
| Explosion Data – Sensitivity to Static Discharge | : Not applicable |

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Wet cement is alkaline. TekFlex® Powder and TekFlex® Liquid react to form a flexible cement based sealant.

Chemical Stability: Stable under recommended handling and storage conditions (see section 7).

Possibility of Hazardous Reactions: Hazardous reactions will not occur.

Conditions to Avoid: Use of product in extremely high or low temperatures will affect set times.

Incompatible Materials: Acids.

Hazardous Decomposition Products: Oxides of calcium and other metal oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not toxic based on mixture ingredients

LD50 and LC50 Data: Refer to individual mixture ingredients

Skin Corrosion/Irritation: Causes skin irritation.

Serious Eye Damage/Irritation: Causes serious eye irritation.

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Teratogenicity: No based on mixture ingredients

Carcinogenicity: No based on mixture ingredients

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: No based on mixture ingredients

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Irritation to the respiratory tract.

Symptoms/Injuries After Skin Contact: Causes skin irritation. Exposure may produce an allergic reaction.

TekFlex® Powder

Safety Data Sheet

Symptoms/Injuries After Eye Contact: Causes serious eye irritation. May lead to eye damage if not treated.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: Repeated and prolonged inhalation may damage lungs.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

| | |
|--------------------------------------|--------------|
| Calcium sulfate (7778-18-9) | |
| LD50 Oral Rat | > 3000 mg/kg |
| Calcium hydroxide (1305-62-0) | |
| LD50 Oral Rat | 7340 mg/kg |

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

| | |
|------------------------------------|---|
| Calcium sulfate (7778-18-9) | |
| LC50 Fish 1 | 2980 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static]) |
| LC 50 Fish 2 | > 1970 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static]) |

Persistence and Degradability Not available

Bioaccumulative Potential

| | |
|--------------------------------------|----------------------|
| Calcium hydroxide (1305-62-0) | |
| BCF fish 1 | (no bioaccumulation) |

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: If this product as supplied becomes a waste, it does not meet the criteria of a hazardous waste as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Dispose of material in accordance with all applicable federal, state/provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator.

SECTION 14: TRANSPORT INFORMATION

14.1 In Accordance with DOT Not regulated for transport

14.2 In Accordance with IMDG Not regulated for transport

14.3 In Accordance with IATA Not regulated for transport

14.4 In Accordance with TDG Not regulated for transport

National Motor Freight Classification

NMFC Name: Cement, Hydraulic **NMFC Number:** 42130 Class: 50

Tariff Classification Number: 4523.90.0000

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

| | |
|---|--|
| TekFlex® Powder | |
| SARA Section 311/312 Hazard Classes | Immediate (acute) health hazard Delayed (chronic) health hazard |
| Cement, portland, chemicals (65997-15-1) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| Calcium sulfate (7778-18-9) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| Cement, alumina, chemicals (65997-16-2) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| Calcium hydroxide (1305-62-0) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |

TekFlex® Powder

Safety Data Sheet

US State Regulations

Cement, portland, chemicals (65997-15-1)

U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
U.S. - Idaho - Occupational Exposure Limits - Mineral Dusts and TWAs
U.S. - Massachusetts - Right To Know List
U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New York - Occupational Exposure Limits - Mineral Dusts
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
U.S. - Oregon - Permissible Exposure Limits - Mineral Dusts and TWAs
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Tennessee - Occupational Exposure Limits - TWAs
U.S. - Texas - Effects Screening Levels - Long Term and Short Term
U.S. - Vermont - Permissible Exposure Limits - TWAs
U.S. - Washington - Permissible Exposure Limits – STELs and TWAs

Calcium sulfate (7778-18-9)

U.S. - Idaho - Occupational Exposure Limits - TWAs
U.S. - Massachusetts - Right To Know List
U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
U.S. - Oregon - Permissible Exposure Limits - TWAs
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Tennessee - Occupational Exposure Limits - TWAs
U.S. - Texas - Effects Screening Levels - Long Term and Short Term
U.S. - Vermont - Permissible Exposure Limits - TWAs
U.S. - Washington - Permissible Exposure Limits – STELs and TWAs

Calcium hydroxide (1305-62-0)

U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
U.S. - Idaho - Occupational Exposure Limits - TWAs
U.S. - Massachusetts - Right To Know List
U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
U.S. - Oregon - Permissible Exposure Limits - TWAs
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Tennessee - Occupational Exposure Limits - TWAs
U.S. - Texas - Effects Screening Levels - Long Term and Short Term
U.S. - Vermont - Permissible Exposure Limits - TWAs

TekFlex® Powder


Safety Data Sheet

U.S. - Washington - Permissible Exposure Limits – STELs and TWAs
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet

Canadian Regulations

TekFlex® Powder

| | |
|----------------------|---|
| WHMIS Classification | Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects |
|----------------------|---|



Cement, portland, chemicals (65997-15-1)

Listed on the Canadian DSL (Domestic Substances List) inventory.
Listed on the Canadian Ingredient Disclosure List

| | |
|----------------------|------------------------------|
| WHMIS Classification | Class E - Corrosive Material |
|----------------------|------------------------------|

Calcium sulfate (7778-18-9)

Listed on the Canadian DSL (Domestic Substances List) inventory.

| | |
|----------------------|---|
| WHMIS Classification | Uncontrolled product according to WHMIS classification criteria |
|----------------------|---|

Cement, alumina, chemicals (65997-16-2)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Calcium hydroxide (1305-62-0)

Listed on the Canadian DSL (Domestic Substances List) inventory.
Listed on the Canadian Ingredient Disclosure List

| | |
|----------------------|------------------------------|
| WHMIS Classification | Class E - Corrosive Material |
|----------------------|------------------------------|

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision date : 02/28/2018

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases: Based on individual ingredients. Refer to Section 2: Hazardous Identification for the Substance or Mixture.

| | |
|---------------|---|
| Eye Irrit. 2A | Serious eye damage/eye irritation Category 2A |
| Skin Irrit. 2 | Skin corrosion/irritation Category 2 |
| Skin Sens. 1 | Skin sensitization Category 1 |
| STOT SE 3 | Specific target organ toxicity (single exposure) Category 3 |
| H315 | Causes skin irritation |
| H317 | May cause an allergic skin reaction |
| H318 | Causes serious eye damage |
| H319 | Causes serious eye irritation |
| H335 | May cause respiratory irritation |

Party Responsible for the Preparation of This Document

Minova USA Inc. SHES Department
Phone Number: 1-502-863-6800

TekFlex® Powder

Safety Data Sheet

All information contained herein and in any supporting documents is provided for informational purposes only and is as accurate and up-to-date as possible at the time of publication. Since Orica and its related entities cannot anticipate or control the conditions under which this information may be used, users must review this information in the specific context of the intended application and must make their own determinations as to the suitability of this information for such users' purposes. To the maximum extent permitted by law, nothing contained herein and in any supporting documents shall be deemed to be an express or implied warranty, and Orica expressly disclaims all warranties and representations, INCLUDING WITHOUT LIMITATION, WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Orica will not be responsible for any loss whatsoever resulting from any use or reliance upon this information.

North America GHS US 2012 & WHMIS