

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations. Revision Date: 03/01/2019 Date of issue: 02/28/2018 Supersedes SDS Date: 02/28/2018 Version 3.0 Revision Impetus: Text and logo format changes.

SECTION 1: IDENTIFICATION

Product Identifier
Product Name: TekFoam
Synonyms: Foamed cement

<u>Intended Use of the Product</u> Foamed cement for cavity filling

Name, Address, and Telephone of the Responsible Party

USA: Canada: Minova USA Inc. Minova

150 Summer Court 576 Arvin Avenue

Georgetown, KY 40324 Stoney Creek, ON - Canada L8E 5P1

T 502-863-6800 For SDS Requests:

Call 1-855-266-7422 or email sds.na@orica.com

www.minovaglobal.com

Emergency Telephone Number

Emergency number : For chemical emergencies (24 hour) involving transportation, spill, leak, release, fire or accidents: IN THE

T 905-643-1166

U.S. or CANADA CALL: CHEMTREC 1-800-424-9300, Minova CCN 14730.

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Skin Irrit. 2 H315 Skin Sens. 1 H317 Eye Irrit. 2A H319 STOT SE3 H335

<u>Label Elements</u>

GHS-US Labeling

Hazard Pictograms (GHS-US)





Signal Word (GHS-US) : Danger

Hazard Statements (GHS-US) : H315 – Causes skin irritation.

H317 – May cause an allergic skin reaction.H319 – Causes serious eye irritation.H335 – May cause respiratory irritation.

Precautionary Statements (GHS-US) : P261 - Avoid breathing dust.

P264 - Wash hands, forearms, and exposed areas thoroughly after handling.

P280 - Wear protective clothing, protective gloves, eye protection. P302+P352 – If on skin: Wash with plenty of soap and water.

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P310 - Immediately call a POISON CENTER or doctor/physician.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse.

03/01/2019 EN (English US) 1/10

Safety Data Sheet

<u>Other Hazards</u> Contains Portland cement or other caustic material which may cause an allergic skin reaction in sensitive individuals. Wet cement can dry the skin and cause chemical burns.

Other Hazards Not Contributing to the Classification: None

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Name	Product identifier	% (w/w)	Classification (GHS-US)
Calcium sulfate	(CAS No) 7778-18-9	10 - 30	Skin Irrit. 2, H315
			Eye Dam. 1, H318
Cement, alumina, chemicals	(CAS No) 65997-16-2	10 - 30	Eye Irrit. 2A, H319
Cement, portland, chemicals	(CAS No) 65997-15-1	10 - 30	Skin Irrit. 2, H315
			Eye Dam. 1, H318
			Skin Sens. 1, H317
			STOT SE 3, H335
Calcium hydroxide	(CAS No) 1305-62-0	1 - 5	Skin Irrit. 2, H315
			Eye Dam. 1, H318
			STOT SE 3, H335
Sodium carbonate	(CAS No) 497-19-8	1 - 5	Eye Irrit. 2A, H319
Aluminum sulfate	(CAS No) 10043-01-3	1 - 5	Met. Corr. 1, H290
			Acute Tox. 4 (Oral), H302
			Eye Dam. 1, H318
			Aquatic Acute 3, H402
Lithium carbonate	(CAS No) 554-13-2	0.1 - 1	Acute Tox. 4 (Oral), H302
			Eye Irrit. 2A, H319

A range of concentration as prescribed by the Controlled Products Regulations has been used where necessary, due to varying composition. Full text of H-phrases: see section 16.

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible). **Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Keep at rest and in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin Contact: Remove contaminated clothing. Rinse off affected area with water. Obtain medical attention if irritation develops or persists.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes. Immediately call a doctor/physician.

Ingestion: Rinse mouth. Do not induce vomiting. If spontaneous vomiting occurs, have victim lean forward with head positioned between legs to avoid breathing in of vomit, rinse mouth and have victim drink plenty of water. Immediately call a POISON CENTER or doctor/physician. Never give anything by mouth to an unconscious person.

Most Important Symptoms and Effects Both Acute and Delayed

General: Irritation can be serious and damage eyes, respiratory system and skin. May cause an allergic skin reaction.

Inhalation: Causes irritation to the respiratory tract.

Skin Contact: Causes skin irritation. Exposure may produce an allergic reaction.

Eye Contact: Causes serious eye irritation.

Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: Repeated and prolonged inhalation may damage lungs.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Safety Data Sheet

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not flammable.

Explosion Hazard: Product is not explosive.

Reactivity: Wet cement is alkaline.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire. **Firefighting Instructions:** Use water spray or fog for cooling exposed containers. **Protection During Firefighting:** Firefighters should wear full protective gear.

Hazardous Combustion Products: Oxides of calcium and other metal oxides. As in all fires toxic and noxious fumes.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not get in eyes or on skin. Do not breathe dust.

For Non-Emergency Personnel

Protective Equipment: Use appropriate Personal Protection Equipment (PPE).

Emergency Procedures: Evacuate danger area.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: In the event of a spill or leak of material sweep up material. Avoid creating excessive dust and as with all

spills, minimize material from entering water systems.

Environmental Precautions

Avoid release to the environment.

Methods and Material for Containment and Cleaning Up

For Containment: Avoid generation of dust during clean-up of spills.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: Good housekeeping is needed during storage, transfer, handling, and use of the is material to avoid excessive dust accumulation. Never add material to this product unless instructed by Minova.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Always wash your hands immediately after handling this product, and once again before leaving the workplace.

Conditions for Safe Storage, Including Any Incompatibilities

Storage Conditions: Store in a dry, cool place.

Incompatible Materials: Acids.

Specific End Use(s)

Foamed cement for cavity filling

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Cement, portland, chemicals (65997-15-1)		
USA ACGIH	ACGIH TWA (mg/m³)	1 mg/m³
USA OSHA	OSHA PEL (TWA) (mg/m³)	5 mg/m³
USA NIOSH	NIOSH REL (TWA) (mg/m³)	5 mg/m³
USA IDLH	US IDLH (mg/m³)	5000 mg/m ³
Alberta	OEL TWA (mg/m³)	10 mg/m³
British Columbia	OEL TWA (mg/m³)	3 mg/m³ (particulate matter containing no Asbestos and <1%
		Crystalline silica)
Manitoba	OEL TWA (mg/m³)	1 mg/m³
New Brunswick	OEL TWA (mg/m³)	10 mg/m ³
Newfoundland & Labrador	OEL TWA (mg/m³)	1 mg/m³

03/01/2019 EN (English US) 3/10

Safety Data Sheet

Salety Data Slicet		
Nova Scotia	OEL TWA (mg/m³)	1 mg/m³
Nunavut	OEL TWA (mg/m³)	10 mg/m³ (total mass)
Northwest Territories	OEL TWA (mg/m³)	10 mg/m³ (total mass)
Ontario	OEL TWA (mg/m³)	1 mg/m³ (containing no Asbestos and <1% Crystalline silica)
Prince Edward Island	OEL TWA (mg/m³)	1 mg/m³ (particulate matter containing no Asbestos and <1%
	, 3, ,	Crystalline silica)
Québec	VEMP (mg/m³)	5 mg/m³ (containing no Asbestos and <1% Crystalline silica)
Saskatchewan	OEL STEL (mg/m³)	20 mg/m ³
Saskatchewan	OEL TWA (mg/m³)	10 mg/m ³
Yukon	OEL STEL (mg/m³)	20 mg/m ³
Yukon	OEL TWA (mg/m³)	10 mg/m ³
Calcium sulfate (7778-18-9)		
USA ACGIH	ACGIH TWA (mg/m³)	10 mg/m³
USA OSHA	OSHA PEL (TWA) (mg/m³)	5 mg/m ³
USA NIOSH	NIOSH REL (TWA) (mg/m³)	5 mg/m³
Alberta	OEL TWA (mg/m³)	10 mg/m³
British Columbia	OEL TWA (mg/m³)	10 mg/m³
Manitoba	OEL TWA (mg/m³)	10 mg/m³
New Brunswick	OEL TWA (mg/m³)	10 mg/m³
Newfoundland & Labrador	OEL TWA (mg/m³)	10 mg/m³
Nova Scotia	OEL TWA (mg/m³)	10 mg/m³
Ontario	OEL TWA (mg/m³)	10 mg/m³
Prince Edward Island	OEL TWA (mg/m³)	10 mg/m ³
Québec	VEMP (mg/m³)	5 mg/m³ (containing no Asbestos and <1% Crystalline silica)
Saskatchewan	OEL STEL (mg/m³)	20 mg/m ³
Saskatchewan	OEL TWA (mg/m³)	10 mg/m ³
	, , ,	10 (118/11)
Calcium hydroxide (1305-62	1 -	F / 3
USA ACGIH	ACGIH TWA (mg/m³)	5 mg/m³
USA OSHA	OSHA PEL (TWA) (mg/m³)	5 mg/m³
USA NIOSH	NIOSH REL (TWA) (mg/m³)	5 mg/m³
Alberta	OEL TWA (mg/m³)	5 mg/m³
British Columbia	OEL TWA (mg/m³)	5 mg/m³
Manitoba	OEL TWA (mg/m³)	5 mg/m³
New Brunswick	OEL TWA (mg/m³)	5 mg/m ³
Newfoundland & Labrador	OEL TWA (mg/m³)	5 mg/m³
Nova Scotia	OEL TWA (mg/m³)	5 mg/m³
Nunavut	OEL STEL (mg/m³)	10 mg/m³
Nunavut	OEL TWA (mg/m³)	5 mg/m³
Northwest Territories	OEL STEL (mg/m³)	10 mg/m³
Northwest Territories	OEL TWA (mg/m³)	5 mg/m³
Ontario	OEL TWA (mg/m³)	5 mg/m ³
Prince Edward Island	OEL TWA (mg/m³)	5 mg/m ³
Québec	VEMP (mg/m³)	5 mg/m³
Saskatchewan	OEL STEL (mg/m³)	10 mg/m ³
Saskatchewan	OEL TWA (mg/m³)	5 mg/m ³
Yukon	OEL STEL (mg/m³)	10 mg/m ³
Yukon	OEL TWA (mg/m³)	5 mg/m³

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Safety Data Sheet

Personal Protective Equipment: Gloves. Protective clothing. Safety glasses. Insufficient ventilation: wear respiratory protection.









Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Safety glasses or chemical goggles as appropriate to prevent eye contact.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: Use a NIOSH-approved respirator "dust mask" industy conditions or whenever exposure may exceed

established Occupational Exposure Limits.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State : Solid

Appearance: Grey powderOdor: Not applicableOdor Threshold: Not applicable

pH : 10.5 - 11.5 when mixed with water

Relative Evaporation Rate (butyl acetate=1) Not applicable **Melting Point** Not applicable **Freezing Point** Not applicable **Boiling Point** Not applicable **Flash Point** Not applicable **Auto-ignition Temperature** Not applicable **Decomposition Temperature** Not applicable Flammability (solid, gas) Not applicable **Lower Flammable Limit** Not applicable **Upper Flammable Limit** Not applicable **Vapor Pressure** Not applicable Relative Vapor Density at 20 °C Not applicable **Relative Density** Not applicable **Specific Gravity** Not applicable

Solubility : Slightly soluble in water

Viscosity : Not applicable
Explosion Data – Sensitivity to Mechanical Impact : Not applicable
Explosion Data – Sensitivity to Static Discharge : Not applicable

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Wet cement is alkaline. As such it is incompatible with acids, ammonium salts and phosphorus.

Chemical Stability: Stable under recommended handling and storage conditions (see section 7).

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Use of product in extremely high or low temperatures will affect set times.

Incompatible Materials: Acids.

Hazardous Decomposition Products: Oxides of calcium and other metal oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

<u>Information on Toxicological Effects - Product</u>

Acute Toxicity: Not toxic based on mixtrue ingredients **LD50 and LC50 Data:** Refer to individual mixture ingredients

Skin Corrosion/Irritation: Causes skin irritation

03/01/2019 EN (English US) 5/10

Safety Data Sheet

Serious Eye Damage/Irritation: Causes serious eye irritation.

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Teratogenicity: No based on mixture ingredients **Carcinogenicity:** No based on mixture ingredients

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: No based on mixture ingredients
Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Irritation to the respiratory tract.

Symptoms/Injuries After Skin Contact: Causes skin irritation. Exposure may produce an allergic reaction. **Symptoms/Injuries After Eye Contact:** Causes serious eye damage. May lead to damage if not treated.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: Repeated and prolonged inhalation may damage lungs.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

ED30 and EC30 Data.	
Calcium sulfate (7778-18-9)	
LD50 Oral Rat	> 3000 mg/kg
Calcium hydroxide (1305-62-0)	
LD50 Oral Rat	7340 mg/kg
Sodium carbonate (497-19-8)	
LD50 Oral Rat	4090 mg/kg
LC50 Inhalation Rat (mg/l)	2300 mg/m³ (Exposure time: 2 h)
Aluminum sulfate (10043-01-3)	
LD50 Oral Rat	1930 mg/kg
Lithium carbonate (554-13-2)	
LC50 Inhalation Rat (mg/l)	> 2.17 mg/l/4h

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecology - General

Calcium sulfate (7778-18-9)	
LC50 Fish 1	2980 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
LC 50 Fish 2	> 1970 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
Sodium carbonate (497-19-8)	
LC50 Fish 1	300 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 1	265 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	310 - 1220 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

Persistence and Degradability Not available

Bioaccumulative Potential

Calcium hydroxide (1305-62-0)		
BCF fish 1	(no bioaccumulation)	
Sodium carbonate (497-19-8)		
BCF fish 1	(no bioaccumulation)	
Lithium carbonate (554-13-2)		
BCF fish 1	(no bioaccumulation)	

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

03/01/2019 EN (English US) 6/10

Safety Data Sheet

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: If this product as supplied becomes a waste, it does not meet the criteria of a hazardous waste as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Dispose of material in accordance with all applicable federal, state/provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator.

SECTION 14: TRANSPORT INFORMATION

14.1 In Accordance with DOT Not regulated for transport 14.2 In Accordance with IMDG Not regulated for transport 14.3 In Accordance with IATA Not regulated for transport 14.4 In Accordance with TDG Not regulated for transport

National Motor Freight Classification

NMFC Name: Cement, Hydraulic NMFC Number: 42130 Class: 50

Tariff Classification Number: 2523.90.0000

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

TekFoam		
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard	
	Delayed (chronic) health hazard	
Cement, alumina, chemicals (65997-16-2)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Cement, portland, chemicals (65997-15-1)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Calcium sulfate (7778-18-9)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Calcium hydroxide (1305-62-0)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Sodium carbonate (497-19-8)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Aluminum sulfate (10043-01-3)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Lithium carbonate (554-13-2)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Listed on SARA Section 313 (Specific toxic chemical listings)		
SARA Section 313 - Emission Reporting	1.0 %	

US State Regulations

Lithium carbonate (554-13-2)	
U.S California - Proposition 65 - Developmental Toxicity	WARNING: This product contains chemicals known to the State of
	California to cause birth defects.

Cement, portland, chemicals (65997-15-1)

- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Acceptable Ambient Concentrations
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Emission Levels (ELs)
- U.S. Idaho Occupational Exposure Limits Mineral Dusts
- U.S. Idaho Occupational Exposure Limits TWAs
- U.S. Massachusetts Right To Know List
- U.S. Michigan Occupational Exposure Limits TWAs
- U.S. Minnesota Hazardous Substance List
- U.S. Minnesota Permissible Exposure Limits TWAs
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) 24-Hour

03/01/2019 7/10 EN (English US)

Safety Data Sheet

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New York Occupational Exposure Limits Mineral Dusts
- U.S. North Dakota Air Pollutants Guideline Concentrations 8-Hour
- U.S. Oregon Permissible Exposure Limits Mineral Dusts
- U.S. Oregon Permissible Exposure Limits TWAs
- U.S. Pennsylvania RTK (Right to Know) List
- U.S. Tennessee Occupational Exposure Limits TWAs
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term
- U.S. Vermont Permissible Exposure Limits TWAs
- U.S. Washington Permissible Exposure Limits STELs
- U.S. Washington Permissible Exposure Limits TWAs

Calcium sulfate (7778-18-9)

- U.S. Idaho Occupational Exposure Limits TWAs
- U.S. Massachusetts Right To Know List
- U.S. Michigan Occupational Exposure Limits TWAs
- U.S. Minnesota Hazardous Substance List
- U.S. Minnesota Permissible Exposure Limits TWAs
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) 24-Hour
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) Annual
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. North Dakota Air Pollutants Guideline Concentrations 8-Hour
- U.S. Oregon Permissible Exposure Limits TWAs
- U.S. Pennsylvania RTK (Right to Know) List
- U.S. Tennessee Occupational Exposure Limits TWAs
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term
- U.S. Vermont Permissible Exposure Limits TWAs
- U.S. Washington Permissible Exposure Limits STELs
- U.S. Washington Permissible Exposure Limits TWAs

Calcium hydroxide (1305-62-0)

- U.S. Connecticut Hazardous Air Pollutants HLVs (30 min)
- U.S. Connecticut Hazardous Air Pollutants HLVs (8 hr)
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Acceptable Ambient Concentrations
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Emission Levels (ELs)
- U.S. Idaho Occupational Exposure Limits TWAs
- U.S. Massachusetts Right To Know List
- U.S. Michigan Occupational Exposure Limits TWAs
- U.S. Minnesota Hazardous Substance List
- U.S. Minnesota Permissible Exposure Limits TWAs
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) 24-Hour
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) Annual
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. North Dakota Air Pollutants Guideline Concentrations 8-Hour
- U.S. Oregon Permissible Exposure Limits TWAs
- U.S. Pennsylvania RTK (Right to Know) List
- U.S. Tennessee Occupational Exposure Limits TWAs
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term
- U.S. Vermont Permissible Exposure Limits TWAs
- U.S. Washington Permissible Exposure Limits STELs
- U.S. Washington Permissible Exposure Limits TWAs
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 25 Feet to Less Than 40 Feet

03/01/2019 EN (English US) 8/10

Safety Data Sheet

- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 40 Feet to Less Than 75 Feet
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 75 Feet or Greater
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights Less Than 25 Feet

Sodium carbonate (497-19-8)

- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

Aluminum sulfate (10043-01-3)

- U.S. Delaware Pollutant Discharge Requirements Reportable Quantities
- U.S. Louisiana Reportable Quantity List for Pollutants
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 2
- U.S. Massachusetts Oil & Hazardous Material List Reportable Quantity
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 2
- U.S. Massachusetts Right To Know List
- U.S. Massachusetts Toxics Use Reduction Act
- U.S. Michigan Polluting Materials List
- U.S. New Jersey Discharge Prevention List of Hazardous Substances
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List
- U.S. New York Reporting of Releases Part 597 List of Hazardous Substances
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

Lithium carbonate (554-13-2)

- U.S. Delaware Pollutant Discharge Requirements Reportable Quantities
- U.S. Maine Chemicals of High Concern
- U.S. Massachusetts Right To Know List
- U.S. Massachusetts Toxics Use Reduction Act
- U.S. Minnesota Chemicals of High Concern
- U.S. New Jersey Discharge Prevention List of Hazardous Substances
- U.S. New Jersey Environmental Hazardous Substances List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List

Canadian Regulations

TekFoam WHMIS Classification Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects



Cement, alumina, chemicals (65997-16-2)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Cement, portland, chemicals (65997-15-1)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Listed on the Canadian Ingredient Disclosure List

WHMIS Classification Class E - Corrosive Material

Calcium sulfate (7778-18-9)

Listed on the Canadian DSL (Domestic Substances List) inventory.

03/01/2019 EN (English US) 9/10

Safety Data Sheet

WHMIS Classification	Uncontrolled product according to WHMIS classification criteria		
Calcium hydroxide (1305-62-0)			
Listed on the Canadian DSL (Domestic Substances List) inventory.			
Listed on the Canadian Ingredient Disclosure List			
WHMIS Classification	Class E - Corrosive Material		
Sodium carbonate (497-19-8)			
Listed on the Canadian DSL (Domestic Substances List) inventory.			
Listed on the Canadian Ingred	Listed on the Canadian Ingredient Disclosure List		
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects		
	Class E - Corrosive Material		
Aluminum sulfate (10043-01-	3)		
Listed on the Canadian DSL (Domestic Substances List) inventory.			
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects		
	Class E - Corrosive Material		
Lithium carbonate (554-13-2)			
Listed on the Canadian DSL (D	Listed on the Canadian DSL (Domestic Substances List) inventory.		
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria		

SECTION 16: OTHER INFORMATION

Revision date : 03/01/2019

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA

Hazard Communication Standard 29 CFR 1910.1200 and the Hazardous Products Regulations

(WHMIS 2015).

GHS Full Text Phrases: Based on individual ingredients. Refer to Section 2: Hazardous Identification for the Substance or Mixture.

Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H335	May cause respiratory irritation

Party Responsible for the Preparation of This Document

Minova USA Inc. SHES Department Phone Number: 1-502-863-6800

All information contained herein and in any supporting documents is provided for informational purposes only and is as accurate and up-to-date as possible at the time of publication. Since Orica and its related entities cannot anticipate or control the conditions under which this information may be used, users must review this information in the specific context of the intended application and must make their own determinations as to the suitability of this information for such users' purposes. To the maximum extent permitted by law, nothing contained herein and in any supporting documents shall be deemed to be an express or implied warranty, and Orica expressly disclaims all warranties and representations, INCLUDING WITHOUT LIMITATION, WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Orica will not be responsible for any loss whatsoever resulting from any use or reliance upon this information.

North America GHS US 2012 & WHMIS